

UNCLASSIFIED

AD NUMBER	
AD010030	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO:	Approved for public release; distribution is unlimited.
FROM:	Distribution authorized to DoD only; Administrative/Operational Use; 27 FEB 1953. Other requests shall be referred to Office of the Chief of Ordnance, Department of the Army, Washington, DC 20310. Pre-dates formal DoD distribution statements. Treat as DoD only.
AUTHORITY	
USAMC ltr dtd 26 Mar 1981; USAMC ltr dtd 26 Mar 1981	

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD \_\_\_\_\_

DEFENSE DOCUMENTATION CENTER  
FOR  
SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA

DOWNGRADED AT 3 YEAR INTERVALS:  
DECLASSIFIED AFTER 12 YEARS  
DOD DIR 5200.10



UNCLASSIFIED

**THIS REPORT HAS BEEN DECLASSIFIED  
AND CLEARED FOR PUBLIC RELEASE.**

**DISTRIBUTION A**  
**APPROVED FOR PUBLIC RELEASE ;  
DISTRIBUTION UNLIMITED .**

**CONFIDENTIAL  
Security Information**

**NORTH AMERICAN INSTRUMENTS INC.**

**PRELIMINARY WIND STUDIES FOR LOKI**

**By**

**Bernard Helfand**

**Design and Development of a Wind Correction Computer  
For Use with M33 Director  
in the Fire Control for LOKI Rockets**

**February 27, 1953**

**Quarterly Report for Second Quarter  
October 1, 1952 to December 30, 1952**

**Contract No. DA-04-495-Ord-352  
Sub-RAD Order No. ORDTU 2-1106-7  
Ordnance Project No. TU2-1012**

**CONFIDENTIAL  
Security Information**

**CONFIDENTIAL**  
**Security Information**

**TABLE OF CONTENTS**

	<u>Page</u>
Introduction	1
Discussion	2
Conclusions	6

**ILLUSTRATIONS**

- Fig. 1           LOKI Crosswind Influence Function
- Fig. 2           Deviation at Burnout Due to Unit Crosswind
- Figs. 3-6       Wind Profile Sequences
- Figs. 7A-10A     Time History of Wind and Deviation at Burnout
- Figs. 7B-10B     Time History of 4-Second Average Wind and  
                    Deviation at Burnout
- Figs. 11A-14A    Deviation at Burnout vs. Wind
- Figs. 11B-14B    Deviation at Burnout vs. 4-Second Average Wind
- Fig. 15          Departure from Regression Line - Wind at 50-foot  
                    Level
- Fig. 16          Departure from Regression Line - 4-Second Average  
                    Wind at 50-foot Level

**CONFIDENTIAL**  
**Security Information**

CONFIDENTIAL  
Security Information

INTRODUCTION

The design of a computer system for LOKI which will automatically correct for the effect of wind during the boost phase of flight requires a knowledge of the function relating deviation at burnout with the wind distribution along the trajectory as well as a knowledge of the nature of the wind distribution at the time of flight. The function relating deviation at burnout with the distributed wind was determined in an earlier report on this project, Ref. 1, and was shown as a relation between influence coefficient (angular deviation of flight path direction at burnout from direction at launch per unit crosswind per unit distance increment along trajectory) and distance of rocket from launcher.

The purpose of this report is to examine the effects of arbitrary and observed wind distributions on LOKI, based on the foregoing influence function, with a view to establishing the basis for a practical field wind measuring technique to gather and transmit wind information to the correction computer.

From time series of wind profiles obtained experimentally, burnout deviations are computed and compared with concurrent winds at fixed levels for both instantaneous and time averaged winds to determine the feasibility of a correction method based on a linear relationship between burnout deviation and wind at one level. Although the available wind data were limited to about 150 cases and covered only the first 250 feet of trajectory accounting for 50% of the total cor-

CONFIDENTIAL  
Security Information

**CONFIDENTIAL**  
**Security Information**

-2-

rection, the high correlations found indicate a strong possibility of success for this method. Further work with more extensive observations will be necessary to substantiate these results and to explore other possibilities for wind specification such as block (space and time) averaging and to provide proportionality constants and limits of accuracy for working computer systems.

**DISCUSSION**

The total flight path angular deviation of LOKI due to wind during burning is given by:

$$\delta = \int_0^s [\Delta \gamma_f(s) W(s)] ds$$

where  $\Delta \gamma_f(s)$  is the wind influence coefficient and  $W(s)$  is the wind component perpendicular to the trajectory at a point on the trajectory distant  $s$  from the launcher. In the derivation of the  $\Delta \gamma_f(s)$  function, Ref. 1, the wind component along the trajectory was assumed to be negligible in its effect on deviation at burnout, due to the high speed and forward acceleration of LOKI. A plot of  $\Delta \gamma_f(s)$  is shown in Fig. 1.

The cumulative effect of a constant crosswind during burning is shown in Fig. 2 when  $\delta$  is plotted against  $s$  for unit crosswind. Of the total deviation 0.8 mil, 50% is due to the first 250 feet of trajectory, while 94% is accounted for by the first 1000 feet.

**CONFIDENTIAL**  
**Security Information**

**CONFIDENTIAL**  
**Security Information**

-3-

An initial study of  $\delta$  variation was made using a synthetic wind made up of a steady 1/7 power law component and a superimposed sinusoidal gust component, varying wave length and amplitude. The assumed wind is described by:

$$W(s) = W_0 \left( \frac{s}{s_0} \right)^{\frac{1}{7}} \left[ 1 + K \sin \frac{2\pi}{\lambda} s \right], \quad 0 < s < 1500 \text{ ft.}$$

$$W(s) = W_{1500}, \quad 1500 < s < 2000 \text{ ft.}$$

where  $W(s)$  = wind velocity at height  $s$

$s_0$  = reference height, 50 ft. at which

$\lambda$  = wave length of gust component, ft.

$K$  = gust amplitude factor

Values of deviation were computed for

$$\lambda = 50, 100, 200 \text{ and } 400 \text{ ft. with } K = 0, 0.5 \text{ and } 1.0$$

Results are summarized in the following table

		Relative Deviation at Burnout		
L	K	0	0.5	1.0
50	1	1.014	1.029	
100	1	1.027	1.043	
200	1	1.004	1.010	
400	1	1.042	1.084	

**CONFIDENTIAL**  
**Security Information**

**CONFIDENTIAL**  
Security Information

-4-

Significant effects would undoubtedly be observed at values of  $\lambda$  greater than 400 feet and with the introduction of gust phase angle as a parameter. This investigation was not pursued further at this time, however, since the chief interest lies in the application to sampling requirements. It is evident from the small effect of the gust component on  $\delta$  for  $\lambda = 50$  and 100 feet, that for practical purposes the wind will be completely described by measurements at 25-foot intervals, the intervals that occur in the experimental data to be discussed.

From data published in Refs. 2 and 3, the vertical wind profiles shown in Figs. 3 to 6 were obtained. These show the time histories at one-second intervals, of the velocity distribution with height. The original measurements were made with pressure plate anemometers described in the foregoing references having an effective time constant of about 0.1 sec., located at 25-foot intervals on a 250-foot tower. Wind direction was not recorded, and the profiles do not exactly represent the crosswind in a fixed plane that would apply to a vertical trajectory. The assumption of constant direction leads to an exaggerated rather than smoothed profile. Four separate runs are included with velocities ranging from 14 to 54 mph, and all were obtained in winter storms in Michigan.

From the wind profiles, deviation sequences were calculated. The wind values at each measurement point were assumed to describe the wind in a layer ex-

**CONFIDENTIAL**  
Security Information

**CONFIDENTIAL**  
**Security Information**

-5-

tending  $12 \frac{1}{2}$  feet to either side (histogram distribution). Products of these values and the corresponding influence coefficient were summed to give the contribution of the wind in the first 250 feet of trajectory. This contribution is about 50% of the total that would be obtained if the integration were carried to burnout.

Time histories of deviation are plotted in Figs. 7A to 10A for the four runs along with concurrent winds at the 25, 50, 100, and 150-foot levels. These indicate a trend of wind velocity consistent with deviation. To better show the trend of a four-second average wind (arithmetic mean of the wind at time T, and the previous three observations) is plotted in Figs. 7B - 10B.

Deviation is plotted against wind velocity in Figs. 11A - 14A and against four-second average wind velocity in Figs. 11B - 14B . Regression lines are included determined by a least squares linear fit with Wind the independent variable. The limits within which 90% of the observations fall are also shown. These were determined assuming that the departure of  $\delta$  from the regression line follows a normal Gaussian distribution. Histograms showing the distribution corresponding to Figs. 12A and 12B are shown in Figs. 15 and 16 . The following table summarizes the results:

**CONFIDENTIAL**  
**Security Information**

**CONFIDENTIAL**  
**Security Information**

-6-

Wind Measurement Level	Wind Deviation at Burnout			4-Second Average Wind Deviation at Burnout		
	Regression Line Slope mils/mph	Correlation Coefficient	Deviation Spread for 90% Obs. mils	Regression Line Slope mils/mph	Correlation Coefficient	Deviation Spread for 90% Obs. mils
25	.544	.802	± 4.9	.582	.823	± 4.4
50	.399	.805	± 4.7	.419	.836	± 3.9
100	.488	.901	± 3.3	.491	.896	± 3.2
150	.441	.939	± 2.6	.446	.945	± 2.3

**CONCLUSIONS**

It is apparent from the table that a correction based on the wind velocity at a fixed level and the corresponding regression line slope might be entirely reasonable in view of the small spread in wind deviation. The high correlations at 100 and 150 feet result from the secondary peak in the influence function near 150 feet and possibly from a tendency of the wind profile to "pivot" about this level.

**CONFIDENTIAL**  
**Security Information**

**CONFIDENTIAL**  
**Security Information**

-7-

Although the available wind data were obtained in one locality and covered only the first 250 feet of trajectory, accounting for 50% of the total effect, the high correlations do indicate a strong possibility of success for methods based on simple averages and limited sampling. Further work is being carried on first, to verify the influence function by comparison between experimental ballistic data and concurrent wind observations and second, to extend the statistical study. Large quantities of additional wind profile sequences, extending as far as 1000 feet, will be required for this purpose, and the use of correlation functions to describe the wind may be adopted to simplify the statistical analysis and to make the information generally useful.

**CONFIDENTIAL**  
**Security Information**

**CONFIDENTIAL**  
Security Information

-8-

**REFERENCES**

- Reference      (1) "LOKI Wind Response Analysis" by Donald L. Baker  
                  and Warren L. Phillips, January 15, 1953.
- (2) "Variation of Wind Velocity and Gusts with Height"  
                  by R. H. Sherlock, M. ASCE, Proceedings of Amer-  
                  ican Society of Civil Engineers, Vol. 78, April 1952.
- (3) "Wind Structure in Winter Storms" by R. H. Sherlock  
                  and M. B. Stout, Journal of the Aeronautical Sciences,  
                  Vol. 5, 1937.

**CONFIDENTIAL**  
Security Information

CONFIDENTIAL  
SECURITY INFORMATION





FIGURE 2  
DEVIATION AT BURNOUT  
DUE TO UNIT CROSSWIND




NORTH AMERICAN INSTRUMENTS, INC. Jan. 1953

CONFIDENTIAL  
SECURITY INFORMATION


~~CONFIDENTIAL  
SECURITY INFORMATION~~

160




**CONTINUATION**

CONFIDENTIAL  
SECURITY INFORMATION



**CONFIDENTIAL  
SECURITY INFORMATION**


160  
34° 30' 6



SECURITY INFORMATION

**CONFIDENTIAL  
SECURITY INFORMATION**


- 60 -



SECURITY INFORMATION  
STRUCTURAL

~~CONFIDENTIAL  
SECURITY INFORMATION~~

160  
sec 5006



**CONFIDENTIAL  
SECURITY INFORMATION**

160  
MAY 6 1966

272  
273  
274  
275  
276

278

277

279

280

271  
272  
273  
274  
275

276

277

278

279

280


**SECURITY INFORMATION**  
**CONFIDENTIAL**

*FIGURE 3 - View PARALLEL SEQUENCES  
EFFECTIVE 025  
EFFECTIVE (B)*

*NORTH AMERICAN INSTRUMENTS, INC. MAY 1966*

**CONFIDENTIAL  
SECURITY INFORMATION**


161/008



**SECURITY INFORMATION**


**CONFIDENTIAL  
SECURITY INFORMATION**

卷之三



SECURITY INFORMATION

CONFIDENTIAL  
SECURITY INFORMATION




SECURITY INFORMATION  
SECURITY INFORMATION

005161

**CONFIDENTIAL  
SECURITY INFORMATION**


161  
Sept 4 1968



**SECURITY INFORMATION**  
**CONFIDENTIAL**

~~CONFIDENTIAL  
SECURITY INFORMATION~~


16/  
shuttle




SECURITY INFORMATION

**CONFIDENTIAL  
SECURITY INFORMATION**

161  
she 6000




**CONFIDENTIAL  
SECURITY INFORMATION**



**SECURITY INFORMATION**


**CONFIDENTIAL  
SECURITY INFORMATION**

848/61



SECURITY INFORMATION  
UNCLASSIFIED

**CONFIDENTIAL  
SECURITY INFORMATION**



**CONFIDENTIAL  
SECURITY INFORMATION**

SECURITY INFORMATION

**CONFIDENTIAL  
SECURITY INFORMATION**

162  
set 3 or 10




FIGURE 5c - WIND PROFILE SEQUENCE


SECURITY INFORMATION

**CONFIDENTIAL  
SECURITY INFORMATION**


**SECURITY INFORMATION**  
**CONFIDENTIAL**

**CONFIDENTIAL  
SECURITY INFORMATION**

**SECURITY INFORMATION**

CONFIDENTIAL  
SECURITY INFORMATIONFIGURE 5 - WIND PROFILE SEQUENCE  
RUN 340  
PAPER 3  
(3)

CONFIDENTIAL  
SECURITY INFORMATION



CONFIDENTIAL  
SECURITY INFORMATION

**CONFIDENTIAL  
SECURITY INFORMATION**

**SECURITY INFORMATION  
UNCLASSIFIED**

01/09/2010



~~CONFIDENTIAL~~  
SECURITY INFORMATION

TIME, SEC

WIND SPEED, KM/H

360

350  
340  
330  
320  
310

300

SECURITY INFORMATION  
UNCLASSIFIED

HE-GWT, REET

100

200

300

400

500

600

700

800

900


1000

FIGURE 50 - WIND PROFILE SEQUENCE  
EXN 350  
REFERENCE (3)

North American Insurants, Inc., 1993


~~CONFIDENTIAL  
SECURITY INFORMATION!~~

163  
Sht 1.56




~~SECURITY INFORMATION~~

**CONFIDENTIAL  
SECURITY INFORMATION**



**SECURITY INFORMATION**  
**UNCLASSIFIED**

~~CONFIDENTIAL~~  
SECURITY INFORMATION




~~CONFIDENTIAL~~  
SECURITY INFORMATION



CONFIDENTIAL  
SECURITY INFORMATION

763  
SAC 306



SECURITY INFORMATION  
CONFIDENTIAL

**CONFIDENTIAL  
SECURITY INFORMATION**

163  
SER 6.66

185  
22 10

2

200

**SECURITY INFORMATION  
UNPUBLISHED MATERIAL**

**MAILED 4/27/77**

**Figure 6 - Modem Sequence Trace  
Part 1**

**CONFIDENTIAL  
SECURITY INFORMATION**


A hand-drawn graph on grid paper showing wind speed versus time. The vertical axis (y-axis) is labeled "WIND SPEED. m/sec" and has major tick marks at 0, 120, and 240. The horizontal axis (x-axis) is labeled "TIME" and has major tick marks at 0, 60, 120, 180, and 240. There are two data series plotted:

- The first series consists of solid black dots connected by a solid line. It starts at approximately (0, 10), rises to about (60, 100), dips slightly to (120, 90), rises again to (180, 150), and ends at (240, 180).
- The second series consists of open circles connected by a dashed line. It starts at approximately (0, 10), rises to about (60, 120), dips slightly to (120, 110), rises again to (180, 180), and ends at (240, 220).

The graph shows a general upward trend over time, with both series exhibiting some local fluctuations.

**CONFIDENTIAL**

CONFIDENTIAL  
SECURITY INFORMATION



**CONFIDENTIAL  
SECURITY INFORMATION**





FIGURE 8A - TIME HISTORY OF WIND AND DEVIATION AT BURNOUT  
 RUN 026 (2)


**CONFIDENTIAL**  
SECURITY INFORMATION

**CONFIDENTIAL  
SECURITY INFORMATION**



**CONFIDENTIAL**

**CONFIDENTIAL  
SECURITY INFORMATION**



**CONFIDENTIAL  
SECURITY INFORMATION**


DEPARTMENT OF THE NAVY

WHICH SPEEDS ARE USED.

四

**CONFIDENTIAL**

CONFIDENTIAL  
SECURITY INFORMATION




CONFIDENTIAL

2010 RELEASE UNDER E.O. 14176

**CONFIDENTIAL  
SECURITY INFORMATION**

**CONFIDENTIAL**

~~163~~  
SECURITY INFORMATION



DEVIATION AT BUENOOUT, 6, MILS

CONFIDENTIAL  
SECURITY INFORMATION

## **SECURITY INFORMATION**

~~CONFIDENTIAL  
SECURITY INFORMATION~~

**SECURITY INFORMATION**

ମେଲି


卷四

卷之三

DEVIATION AT EURUOUT, 6, MILES

~~CONFIDENTIAL  
SECURITY INFORMATION~~

SECURITY INFORMATION



MAINTAIN SPEED AT 30000 FT SECURE AIRSPACE AND

20000 FT

ROUTE 128 - DEVIATION AT BUDAPEST

# **SECURITY INFORMATION**

A large grid of squares, approximately 20 columns by 30 rows, filled with handwritten black numbers. The numbers are mostly single digits (1-9) and some two-digit numbers like 10, 11, etc. A large, hand-drawn 'X' is drawn across the grid, centered vertically and horizontally. In the bottom right corner of the grid, there is a small, separate drawing of a figure standing on a base, holding a long staff or pole.


DEVIATION AT EUGEOU, 6 MILES

~~CONFIDENTIAL~~  
~~URGENT INFORMATION~~

## **SECURITY INFORMATION**


~~CONFIDENTIAL  
SECURITY INFORMATION~~

SECURITY INFORMATION



CONFIDENTIAL  
SECURITY INFORMATION

76  
SECURITY INFORMATION



DEVIATION AT SURFACE 0, MILES

CONFIDENTIAL  
SECURITY INFORMATION

CONFIDENTIAL  
SECURITY INFORMATION

CONFIDENTIAL  
SECURITY INFORMATION